

WOODWORKING DUST COLLECTION HOSE

Dust Collection Hose

T-7

D M

Size: 1.5" to 24"
Length: 25', 50' (up to 12")
Temp Range: -60° to 275°



Medium weight thermoplastic rubber hose reinforced with a spring steel wire helix. Traditional all-purpose dust collection and ventilation hose.

Flx-Thane® LD

A F D

Size: 2" to 18"
Length: 25'
Temp Range: -65° to 225°



Light weight polyurethane hose reinforced with a bronze coated spring steel wire helix.

Flx-Thane® MD

M

Size: 2" to 18"
Length: 25', 50' (up to 12")
Temp Range: -65° to 225°



Medium weight polyurethane hose reinforced with a bronze coated spring steel wire helix.

Static Control Hose

Flx-Thane® LD-SD

A F D

Size: 2" to 12"
Length: 25'
Temp Range: -65° to 225°



Light weight clear static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix. Surface resistivity level of: 10^8 - 10^{10} Ohms/Square.

Flx-Thane® SD

M

Size: 2" to 12"
Length: 25', 50' (up to 12")
Temp Range: -65° to 225°



Medium weight static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix. Surface resistivity level of: 10^8 - 10^{10} Ohms/Square.

FlexStat®

F D M

Size: 1" to 8"
Length: 25', 50'
Temp Range: -40° to 200°




Specially formulated static dissipative polyurethane hose reinforced with a rigid ABS helix and an embedded copper grounding wire. Surface resistivity level of: 10^8 - 10^{10} Ohms/Square.

CNC Vacuum Hose & Accessories

Flex-Tube® PU 60 HF

M

Size: 2" to 8"
Length: 25', 50'
Temp Range: -40° to 200°



Highly flexible very heavy weight thermoplastic polyether polyurethane hose with a rigid external ABS helix.


Flex-Tube® Bridge Clamps

- Specially designed stainless steel band and welded stainless steel bridge with stainless steel screw
- Fits over helix creating a leak proof seal
- Available in sizes 4" to 12"



Flex-Tube® Swivel Connector

- Designed to make it easier to maneuver longer (connected) lengths of hose
- Available in sizes 2", 2.5", 3", 4", 6"
- Made with high strength polyurethane to withstand application abuse
- Secure with Flex-Tube bridge clamps or T-bolts (2", 2.5" & 3")



Shop Vacuum Clean-Up Kits

Industrial MRO General Pick-Up Kit

Designed to fit all standard Wet/Dry Vacuums

- 1.5" x 15' StatPath® Plus Hose with Swivel Cuff and Inlet Adapter
- 4" Utility Tool
- 11" Crevice Tool



Commercial MRO General Pick-Up Kit

Designed to fit all standard Wet/Dry Vacuums

- 1.5" x 12' Flx Plus Hose with Swivel Cuff and Inlet Adapter
- 4" Utility Tool
- 11" Crevice Tool



Commercial MRO General Pick-Up Kit POP Display

10 kits, each kit includes:

- 1.5" x 12' Flx Plus Hose with Swivel Cuff and Inlet Adapter
- 4" Utility Tool
- 11" Crevice Tool

